



-GLP-

**GLP**  
INSTALLATION

# FUSION STICK FS10

## DESCRIPTION

Because of its intelligent connector system the FUSION Stick creates seamless light lines – horizontal or vertical, indoor as well as outdoor. The most so called “bars” are too weak to produce a homogenous area light.

With the FUSION Stick it is no problem to change the reflection angle between beam to wide flood or asymmetrical. Even when using diffuser plates the FUSION Stick creates more than enough light power and even works fanless.

Art. No.: 4900213



## KEY FEATURES



### LIGHT SOURCE

10 x 15 Watt RGBW LED



### PIXEL PITCH

continuous alignment between fixtures



### IP65

suited for Outdoor use

## DETAILS

Further information, pictures, and technical details as well as downloads for FUSION Stick FS10 at our website: [www.glp.de](http://www.glp.de)

Direct-Link:



IP65

DMX

CRMX




7.5 kg



RGBW

# FUSION STICK FS10



## TECHNICAL DATA

### LIGHT SOURCE

LED Type	RGBW
Lifetime	20,000 h
LED Count	10

### OPTICAL SYSTEM

Beam angle	6°
ConsistentColor™ Optics	

### EFFECTS

Color mixing	RGBW, 8-bit or 16-bit
Color wheel	virtual, 39 colors including whites (2,700; 4,200; 5,600; 7,200; 8,000 K)
Dimmer	0–100% electronic, regular and random strobe and pulse effects, selectable dimmer curves
internal effects	Pixel Mapping, pattern effects with variable speed

### ELECTRICAL SPECIFICATIONS

Mains voltage	100–240 VAC / 50–60 Hz
Power (@ 230V)	170 W

### DIMENSIONS & WEIGHT

Height	231 mm / 9.09 in
Width	525 mm / 20.67 in
Depth	90 mm / 3.54 in
Weight	7.5 kg / 16.54 lbs

## AVAILABLE ACCESSORIES

PRODUCT	DESCRIPTION	ART. NO.
Base Plate FS20/FS10	for FUSION Stick FS10; 40 x 40 cm, material: steel	4930001
Diffusor Filter 20° FS10	for FUSION Stick FS10; length: 50 cm	4930112
Omega Bracket FS20/FS10	for FUSION Stick FS10	4930009
Vertical Adapter FS20/FS10	for FUSION Stick FS10; vertical installation, hanging or standing; without Bracket	4930109
Glare Shield FS10	for FUSION Stick FS10; length: 50 cm	4930116